

HOFMANN®



SOET9000

9K variolift™ Double-Scissor

General-Purpose Lift

9K variolift™ Double-Scissor

The Hofmann 9K variolift Double-Scissor General-Purpose lift is designed to accommodate a wide range of vehicles. It's low-profile design allows for easy drive-over or it can be installed as a flush-mount.



SOET9000

Features

- Lifts straight up - 5.3" low to 79.75" high.
- Open front and rear with no crossmember for maximum accessibility.
- Dual hydraulic synchronization.
- 18 mechanical locking positions with air-actuated release.
- Non-slip textured lifting pad surface.
- Extendible lifting pad, from 61 1/4" to 81 1/2".
- Surface-mount or flush-mount configurations.
- ALI/ETL Certified to the current ANSI ALCTV:2006 standard.



Approach ramps can be raised and used to extend the surface length of the lifting pads.



General-Purpose Lift

Specifications

Lifting Capacity	9,000 lbs.
Surface-Mount Max. Lifting Height	79.75"
Flush-Mount Max. Lifting Height	74.5"
Surface-Mount Lowered Height	5.3"
Flush-Mount Lowered Height	0"
Lifting Pad Width	25.5"
Overall Width	82.5"
Lifting Pad Length	61.25"
Console Dimensions (DxWxH)	12.3" x 14.9" x 40.5"
Lifting Time (with full load)	53 seconds
Air Supply Requirements	90 PSI
Shipping Weight	2,700 lbs.
Power Requirements*:	230V, 1Ph, 60Hz

Optional Accessories

SOE-VZ975586	Flat Rubber Plates
SOE-VZ970045	Ductile Plastic Blocks
SOE-VZ975074	Hard Plastic Blocks
SOE-VZ970133	Foundation Insert Plates (for Flush-Mount)
SOE-VZ970127	Aluminum Transverse Beam (3,300 lbs)
SOE-VZ970125	Drive-Over Ramps
SOE-VZ970052	Hydraulic/Pneumatic Hose Extension Set

Hofmann manufactures a complete line of wheel service equipment.



Portable Imaging Alignment Systems

HOFMANN®

USA

309 Exchange Avenue • Conway, AR 72032
 (800) 251-4500 • (501) 505-2662
 Fax (501) 450-2085 • www.hofmann-usa.com

Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
 (800) 267-2185
 Fax (905) 821-2073 • www.hofmann.ca