

# HOFMANN®



**geodyna™ 2300m**

**WHEEL BALANCER**

# geodyna™ 2300m

Hofmann has long been the leader in balancing Motorcycle technology. Since 1931, Hofmann balancing machines have been used around the world to balance anything that rotates. These many years of experience led to the development of the geodyna 2300m Motorcycle Wheel Balancer. The geodyna 2300m is easy to use, accurate, rugged, reliable and affordable.

## Features

- Automatic operation, push button start, automatic brake
- One-plane (static) or two-plane (dynamic) balancing
- High-performance accuracy with low speed operation
- Self-calibration by shop personnel eliminates down time & costly service calls
- Special wheel application kits available

## Hofmann, your one-stop manufacturer for Motorcycle/ATV wheel service equipment



Hofmann monty 1520m  
Motorcycle Tire Changer



Hofmann monty 1520emx  
Motorcycle Tire Changer with  
EasyMont Pneumatic Bead Assist



Hofmann geodyna 2300m  
Motorcycle Wheel Balancer

## WHEEL BALANCER

### Specifications

|                               |                        |
|-------------------------------|------------------------|
| Wheel Width:                  | 1" - 20"               |
| Max. Wheel Assembly Width:    | 21"                    |
| Wheel Diameter:               | 8" - 30"               |
| Max. Wheel Assembly Diameter: | 48"                    |
| Max. Wheel Assembly Weight:   | 155 lbs.               |
| Centering Cone Range:         | 17 mm - 45 mm          |
| Shaft Diameter:               | 14 mm                  |
| Measuring Speed:              | 100 RPM                |
| Motor:                        | 1 HP (acceleration HP) |
| Cycle Time:                   | From 6 seconds         |
| Read-Outs:                    | Gram or Ounce          |
| Accuracy:                     | 1g or 0.05 oz          |
| Balancing Modes:              | 2                      |
| Dimensions (DxWxH):           | 16.5" x 29.5" x 40"    |
| Shipping Weight:              | 280 lbs.               |
| Power Requirements:           | 120V, 1Ph, 60 Hz       |

### Standard Accessories

|             |                          |
|-------------|--------------------------|
| 2400551     | Motorcycle balancing kit |
| EAM0005D40A | Calibration Tool         |
| EAM0006G01A | Storage pegs             |
| EAA0247G21A | Wheel width gauge        |

### Optional Accessories

|              |  |
|--------------|--|
| EAA0283D19A  | Automotive car/truck adapter kit       |
| 2000561      | Harley-Davidson 3/4" shaft kit         |
| 35-7805      | 1" shaft kit for wide wheels, 14" long |
| 2003731      | Ducati wheel adapter                   |
| 2001355      | Honda VFR wheel adapter kit            |
| 2001140      | BMW wheel adapter kit                  |
| 2000557      | Sleeve/Cone kit                        |
| EAK0257G76A* | ATV/Quads/Golf Cart centering kit      |

\*Requires EAA0283D19A



USA

309 Exchange Avenue • Conway, AR 72032  
(800) 251-4500 • (501) 505-2662  
Fax (501) 450-2085 • [www.hofmann-usa.com](http://www.hofmann-usa.com)

**HOFMANN®**



Canada



6500 Millcreek Drive • Mississauga, ONT L5N 2W6  
(800) 267-2185  
Fax (905) 821-2073 • [www.hofmann.ca](http://www.hofmann.ca)