

HOFMANN®



monty™ 1520m/1520emx

TIRE CHANGER

monty™ 1520m/1520emx

The Hofmann monty 1520m and 1520emx can handle motorcycle and ATV tires with a maximum wheel width of 13" and wheel clamping diameter from 10" to 21". Optional ATV clamping jaws allows for clamping down to 7". Both tire changers are equipped with standard clamping jaws that allow for changing automotive and light truck tires as well.

Four Jaw Clamping Chuck

These self-centering clamping jaws powered by two pneumatic cylinders allow for tight clamping of motorcycle wheels.

Powerful Bead Breaker

5,954 lbs. of breaking power and a range of up to 12" wide, the monty 1520m/1520emx provides quick and safe loosening of even tough ATV tire beads.

Dual Wheel Clamping Cylinders

Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage.

Upgradeable

EasyMont Pro* features a three-piece design with a Top Roller, Pressing Foot, and Lifting Disc. Each piece provides a specialized function that assists a single operator in mounting/demounting low-profile and high-performance tires.

Innovative Design

The monty 1520m is designed to change all types of motorcycle tires, including tires on the difficult Harley Davidson belt drive wheels. Standard clamping jaws allow for changing automotive and light truck tires as well.

Specially Designed Clamping Jaws

These clamping jaws are designed to eliminate the additional labor involved in removing the brake disc, sprocket, or drive pulley when servicing a wheel. The monty 1520m is equipped with plastic protection over metal jaws to protect wheels from damage. Plastic protection is also provided in the bead tool head.



monty 1520emx

* Standard with monty 1520emx, optional for monty 1520m

TIRE CHANGER

Specifications

Wheel Clamping Diameter:	10" - 21"
Max. Tire Diameter:	40"
Max. Wheel With:	13"
Compressed Air Supply:	100 - 170 psi @ 5 CFM
Bead Breaking Range:	0" - 12"
Bead Loosening Power:	5,954 lbs.
Dimensions (DxWxH):	72"x68"x85"
Shipping Weight:	419 lbs.
Power Requirements:	120V, 1Ph, 60 Hz

Drive Motor/Air Supply Options

Electric (standard)	1 HP
Air (optional)	Available on request, 110 - 170 psi @ 14 CFM

Standard Accessories

EAA0247G05A	Lube bottle/swab
EAA0247G02A	Tire Lever
ST4016079	Protective insert/roller
ST4028566	Motorcycle jaws

Optional Accessories

EAA0329G35A*	EasyMont bead assist device (req 4027351)
4027351*	Mounting adapter kit (for EAA0329G35A)
ST4029446	Automotive adapters (22" outer clamping diam.)
EAA0332G84A	ATV adapters (7" -14" outer clamping diam.)
EAA0247G20A	Composite mount/demount head
EAA0247G04A	Protective cover (for tire lever)
EAA0247G15A	Protective insert - mount/demount head (10)
EAA0304G14A	Wave tire tool
EAA0247G70A	Bead clamp for performance wheels
RTT75N	Premium tire paste

* Accessory standard with monty 1520emx (M1520EMX110A)

HOFMANN® 

USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com

Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca