

HOFMANN®



monty™ 3300 AT Plus

LEVER-LESS TIRE CHANGER

monty™ 3300 AT Plus

The Hofmann monty 3300 AT Plus lever-less high-performance tire changer is designed for high-volume tire shops, multi-bay repair shops and car dealerships. Technicians can effortlessly and safely change standard tires or the most difficult performance tires (low-profile and run-flat tires) on cars, SUV's and light trucks. The monty 3300 AT Plus features a powerful, multi-position bead breaker that delivers 3,000 lbs. of power at the bead shovel, making easy jobs of both the stiffest and softest sidewalls.

Laser Guided Lever-less Tool Head

The monty 3300 AT Plus features a unique bead lifting tool which inserts between the tire and wheel in a simple motion. Exclusive laser-indexing acts as a visual guide when indexing the demount head to the wheel's edge quickly and easily, eliminating wheel contact.

Dual Wheel Clamping Cylinders

Dual pneumatic clamping cylinders control all four clamping jaws, eliminating damage to wheels due to slippage.

Multi-Position Bead Breaker

3,000 lbs. of power at the bead shovel and a range of up to 16" wide. The two-stage pneumatic cylinder provides precise power and can be toggled with the foot pedal as needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the beads!

Built To Last

Heavy, solid 1/2" thick steel clamping table. Rugged steel-reinforced chassis. Rust-proof air cylinders and valves. Compressed air lubricator and regulator on-board - keeps valves and cylinders maintenance-free!

TIRE CHANGER

Specifications

Inner-Wheel Clamping Diameter:	12" - 24"
Outer-Wheel Clamping Diameter:	10" - 24"
Bead Breaker Range:	3" - 16"
Bead Loosening Power:	3,000 lbs.
Maximum Wheel Width:	15"
Maximum Outer Tire Diameter:	40"
Shipping Weight:	875 lbs.
Power Requirements:	120V, 1Ph, 60Hz

Drive Motor/Air Supply Options

Electric (standard)	1 HP
---------------------	------

Standard Accessories

ST4027645	Outside clamping jaw protectors (4 each)
EAA0304G15A	Protective cover for bead breaker shovel
ST4028648	Magic bead pusher
EAA0329G92A	Hex bar with roller attachment
EAA0332G32A	Round Roller Bar
EAA0304G43A	Bead breaker disc (Use with hex bar)
ST0029455	Protective slide cover

Hofmann manufactures a complete line of wheel service equipment.



Combination brake lathes for rotors, drums and flywheels



Wheel Balancers



Scissor and 4-Post Alignment Lifts



Imaging Wheel Alignment Systems

HOFMANN®

USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com

Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca