

# HOFMANN®



**monty™ 4400/4400r**

**TIRE CHANGER**

# monty™ 4400/4400r

Make wheel service for trucks, tractors, off-road and skidder wheels a faster, easier and more profitable part of your business with Hofmann's monty 4400/4400r. These heavy-duty tire changers are designed to mount/demount tires up to 90" in diameter. The monty 4400/4400r features a hydraulically-operated self-centering four jaw chuck with clamping jaws that can clamp from 14" - 44" either from the wheel inside or from the wheel center bore. It also has one-operator capability that allows one person to safely monitor all tire-changing operations. The bead breaker disc and mount/demount heads are combined into one assembly for ease-of-use. This mount/demount head is manually operated on the monty 4400, and is hydraulically controlled via the remote control console on the monty 4400r. The monty 4400/4400r also has a comprehensive training video available showing the actual mounting & demounting techniques for on and off-road wheels.

## Four Jaw Clamping Chuck

These self-centering hydraulically-operated clamping jaws can clamp from 14" - 44" either from the inside of the wheel or the wheel's center bore. Optional jaw extensions increase clamping range to 56".

## One-Man Operation

The remote control console allows one person to safely monitor all tire changing operations.

## Patented Mount/Demount Head Assembly

The bead breaker disc and mount/demount heads are combined into one assembly for ease-of-use. This mount/demount head is manually operated on the monty 4400, and is hydraulically controlled via the remote control console on the monty 4400r.

## Versatility

The 3 HP 2 speed bi-directional chuck motor and heavy-duty hydraulics allow the monty 4400 to handle the toughest tubeless, tube type, single or multi-piece, Budd, and Dayton wheels.

## TIRE CHANGER

### Specifications

Wheel Clamping Diameter:	14" - 44"
Max. Wheel Assembly Width:	90.5"
Max. Wheel Width:	43"
Hydraulic Motor:	2 HP
Chuck Motor:	3 HP
Chuck Spindle Diameter:	5"
Rotational Torque:	2,268 ft. lbs.
Dimensions (WxDxH):	81"x117"x63"
Shipping Weight:	2,085 lbs.
Power Requirements:	200/230V, 3Ph, 50/60 Hz

### Standard Accessories

EAA0247G02A	Tire lever
ST4004461	Large bead lifting lever
ST4002354	Bead mounting lever
ST4014914	Alloy jaw protectors
EAA0329G10A	Wheel clamp pliers

### Optional Accessories

ST4019161	Jaw extensions (up to 56")
ST4022287	Bead roller
ST4021852	Alloy wheel clamp
4008257	Protective alloy jaws
1970995	Tire mounting paste



309 Exchange Avenue • Conway, AR 72032  
(800) 251-4500 • (501) 505-2662  
Fax (501) 450-2085 • [www.hofmann-usa.com](http://www.hofmann-usa.com)



6500 Millcreek Drive • Mississauga, ONT L5N 2W6  
(800) 267-2185  
Fax (905) 821-2073 • [www.hofmann.ca](http://www.hofmann.ca)