

HOFMANN®



monty™ Universal 2

LEVER-LESS TIRE CHANGER

NEW!

HOFMANN *monty*™ UNIVERSAL 2

The innovative minds at Hofmann have designed a “lever-less” tire changer to meet the ever changing demands of tire shops, automotive garages, car dealerships and specialty shops. The Hofmann *monty Universal 2* provides precision movement of the specially designed laser-guided demount tool. Additional standard labor-saving features included on the *monty Universal 2* are: “Zip-Lock” center clamping of the wheel, integrated wheel lift, dual-position disc-style bead breaker, pneumatic bead assist, two-speed drive system and top-side bead inflation.




Wheel Lift



- Designed to assist technician and reduce fatigue.
- Reduces the chance of damaging expensive wheels.

“Zip-Lock” Center Clamping



- Patented wheel clamping system is fast and easy.
- Protective table and centering cones reduce the chance of wheel damage.
- Adjustable working height is perfect for any size tire or technician.

Dual-Position Disc Bead Breaker



Operator control panel.



Polymer disc won't damage wheels or tire sensors.



Locking disc position is quick and accurate on both sides of tire.

Laser-Guided Demount Tool



- Foot pedal control swings demount tool into position.
- Laser guides technician to ensure proper position of demount tool.
- Simple control inserts the demount tool between the wheel flange and tire.
- Bead is lifted over the wheel flange effortlessly.

monty™
Universal 2



Pneumatic Bead Assist



- Maintains top bead in drop-center on difficult performance wheels.
- Reduces the chance of top bead damage.
- Allows one technician to change any wheel.

Two-Speed Drive System



- Foot pedal motor control system delivers the right torque and speed.
- Two speeds: Low speed with high torque, and fast speed with less torque

Top-Side Bead Inflation



- No need to demount wheel from tire changer.
- Inflates difficult wheels quickly and easily.

Specifications

Wheel Diameter Range	12" - 30"
Max. Tire Diameter	47"
Max. Wheel Width	17"
Max. Wheel Weight	154 lbs.
Work Area Dimensions (D x W x H)	69" x 67" x 81"
Shipping Weight	770 lbs.
Air Requirements	110 - 170 PSI
Power Requirements*	120V, 1Ph, 60Hz

Optional Accessories

Reverse-mounted wheel kit	EAA0358G58A
Light-truck wheel kit	EAA0349G06A

For more information on the *monty Universal 2*, standard or optional accessories, contact a Local Sales Representative or visit our web site.



USA

309 Exchange Avenue • Conway, AR 72032
(800) 251-4500 • (501) 505-2662
Fax (501) 450-2085 • www.hofmann-usa.com



Canada

6500 Millcreek Drive • Mississauga, ONT L5N 2W6
(800) 267-2185
Fax (905) 821-2073 • www.hofmann.ca

